

#### Technical Data Sheet

# **CARBOWAX™ SENTRY™ Polyethylene Glycol (PEG)**

1450

Product CARBOWAX™ SENTRY™ Polyethylene Glycol 1450 NF Flake (Inhibited)

CARBOWAX™ SENTRY™ Polyethylene Glycol 1450 NF Molten (Inhibited) CARBOWAX™ SENTRY™ Polyethylene Glycol 1450 NF Molten (Uninhibited)

**Description** Polyethylene Glycol

CAS Number 25322-68-3
Applications Adhesives

Antistatic Agents Chemical Intermediates Creams and Lotions Excipeints: Ointments,

**ILubricants** 

Mold Release Agent Personal Care

**Toothpaste and Dental Products** 

## Typical Physical Properties(1)

	Value
Property	
Physical Form	Waxy solid (Flake)
Average Number of Repeating Oxyethylene Units	32
Range of Average Molecular Weight	1305 – 1595
Range of Average Hydroxyl Number, mg KOH/g	70 – 86
Density, g/cm³ at 60°C	1.09
Melting or Freezing Range, °C	42 – 46
Solubility in Water at 20°C, % by weight	72
Viscosity at 100°C, cSt	26.5
Heat of Fusion, Cal/g	37
Typical properties, not to be construed as specifications	

### **FDA Status**

CARBOWAX™ Polyethylene Glycols are produced to meet the requirements for use under Food Additive Regulations for indirect use as components of articles intended for use in contact with food. It is the responsibility of the user of CARBOWAX™ PEGs and MPEGs to read and understand all current applicable FDA and EPA regulations, as well as any other applicable regulations.

### **Product Stewardship**

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

U.S.

Toll-Free 800 441 4DOW 989 832 1542

International

Europe/Middle East +800 36 94 63 67 Italy +800 783 825 Asia/Pacific +800 77 76 7776 +60 37 958 3392

Latin America +55 115 184-8722 South Africa +800 99 5078

http://www.dow.com/

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.